



HOME PRIDE TILE BONDER

Description

Home Pride Tile Bonder is a single component when mixed with cement it gives ultimate strength for fixing tile on wall & floor. It is recommended for interior and exterior use .

Features and Benefits

- Provides flexibility to cement
- Water curing properties
- Easy to use
- Highly stronger
- Shock & impact resistance

SUITABLE SURFACE

Cement plaster, stone, marble and chip flooring.

Area of Application

Residential & commercial area, interior & exterior, on floor & walls

Mixing

- A. Mix 50kg cement with 1kg HP Tile Bonder & 15ltr. Water.
- B. Mix 25kg cement with 25kg sand with 1kg HP Tile Bonder & 15ltr. Water.

APPLICATION

DIRECTION OF USE

Shelf Life & Storage

12 months, store in dry & cool place

Coverage

It can vary according to different surfaces.

Technical Information

Properties	Result
Pot Life	1½ -2 Hours
Open Time	30 min
Density	17kg/lb
Setting time	1 Day
Full Strength	14 days
Shear Strength	14.4 KN

Packing

300gm & 1kg

Color

White

CERTIFICATION

ISI TYPE I

Availability

Home Pride Adhesive Pvt. Ltd.
H-533, RIICO Industrial area, Ph-I
Bhiwadi, Distt. Alwar (Rajasthan)

Customer Care no: 1800-11-1818
(Toll Free)

Email: homeprideadhesive@gmail.com
www.homeprideadhesive.com

Price

Contact Home Pride Dealer in your area.

Technical Services

Home Pride Adhesive Pvt. Ltd.
H-533, RIICO Industrial area, Phase-I
Bhiwadi , Distt. Alwar (Rajasthan).

Home is everybody's pride so make sure you use Home Pride.



HOME PRIDE TILE BONDER

Specifications subject to change without notification .Actual field performance will depend on the type of tile/stone/brick used, installation methods and site condition.

Home is everybody's pride so make sure you use Home Pride.