



TECHNICAL INFORMATION

**General**

Display : 7 inch Colour TFT  
 Display area : 150 mm x 90 mm  
 Dimensions : H280 x W 330 x D220 mm (Max) without Paddle  
 Weight : Approx. 6 Kgs. Max.

**Power Supply**

Input : 150 - 270 VAC, 50 Hz, 1 Ø  
 Battery : 12 V 4.5Ah, Rechargeable  
 Battery capacity : 3hours for monitor & 70-100 shocks on single charge  
 LED indicator : Low battery and battery charging  
 Power consumption: 30 Watts (max.) in ECG mode

**Environmental**

Operating Temp. : -5 C to +50 C  
 Humidity : up to 95 % non-condensing

**Defib**

Operating Mode : Manual  
 Waveform : Biphasic  
 Energy : 2 to 200 joules in 12 steps selection  
 Synchronous : Energy delivery begins within 60 ms of the QRS Peak  
 Charging Time : Less than 8 seconds  
 Paddle Assembly : External paddle assembly with coil retractable high voltage cable. Adults & Pediatric paddle integrated to same handle

Check Mode : Manual test mode  
 Operation : By front Panel Keyboard, Encoder & ON-OFF by front Panel Push button

**AED Mode OPTIONAL**

Wave form : Biphasic  
 AED Shock Series : Energy level from 150 to 200J  
 Charge Command : Automatic after identifying arrhythmia  
 Shock Command : front panel button, shock  
 Charging Time : Less than 8 Sec  
 Controls : Analyze, Pause  
 Defibrillation Electrode : Malfunction, Self adhesive, adult electrodes  
 Voice and Text prompts: Voice and text prompts to guide user

**PACER OPTIONAL**

Wave form : Monophasic  
 Modes : Demand or Non Demand  
 Amplitude : From 10mA to 150 mA (resolution of 10 mA),  
 Pulse Width : 40 ms (+/- 1ms)  
 Frequency : From 20 ppm to 250 ppm (increments of 1 ppm),  
 Refractory period : 340 ms (from 30 to 80 ppm); 240 ms (from 90 to 180 ppm). Maximum output voltage: 150 V.  
 Impedance range : 200ohm to 1 k ohm

**ECG**

Frequency response: 0.5 Hz to 35 Hz  
 Patient isolation : Optical isolation  
 Lead selection : Lead I, II and III  
 Gain setting : 0.5, 1.0 and 2.0  
 CMRR : > 90 db  
 Sweep Speed : 12.5, 25.0, 50.0 mm/sec  
 Digital filter : Digital signal processing for good quality of ECG

**Heart Rate**

Range : 10 - 250 BPM  
 Accuracy : +/- 2 BPM  
 Resolution : 1 BPM  
 Tone : Beep on every QRS detected  
 Low alarm limit range : 10 - 250 (step of 1)  
 High alarm limit range : 10 - 250 (step of 1)

**SpO2 OPTIONAL**

Range : 0 - 100%.  
 Accuracy : 70 - 100% +/-2% , 50 - 69% +/-3 %.  
 Pulse rate : displayed when HR is deselected.  
 Pulse beep : Stepless volume control.  
 PR Range : 10 to 250 bpm  
 Pitch variation with change in oxygen saturation.

**NIBP OPTIONAL**

Method : Oscillometric.  
 NIBP interval : User selectable - 3 min to 120 min  
 Modes : Manual, auto.  
 Cuff deflation : Automatic.  
 Safety features : Automatic deflation if cuff pressure exceeds 280 mmHg  
 Range : 10 - 250 mmHg  
 NIBP Status : "Ready"- when not taking reading  
 "Measuring"-when taking reading  
 "Error"- if reading could not be taken due to some error while measuring

Patient Type : Adult, Pediatric, Neonate

**Printer**

Paper Type : Thermal paper 50/55mm width, 20 meters length for 2 inch printer  
 Event Printing : Prints 5 Seconds pre & post ECG with Date, Time, Energy and mode, Shock Status  
 ECG in Defib Mode : Prints last 10sec ECG through paddle  
 Print Annotates in Defib Mode : Time, Date, Mode, Lead name, Gain, Sweep speed  
 ECG in Monitor Mode: Prints last 10 ECG through cable  
 Print Annotates in Monitor Mode : Time, Date, selected Lead name, Gain, Sweep speed  
 Manual Defib Check Mode : Prints the status of Shock, Energy, Date and Time

Monitor Defibrillator



CARDIOMAX

MEDI+ON Healthcare

Marketed & Service by :

**MEDI+ON Healthcare**

Corporate office  
**MEDION HEALTHCARE PVT. LTD**  
 201, Shiv Ind. Estate, K.B.B. Marg,  
 Chinchpokli (east),  
 Mumbai 400 012. INDIA.  
 Tel. : + 91 - 22 - 2377 1737  
 Fax : + 91 - 22 - 2377 1734  
 Email : sales@medion.co.in  
 http://www.medion.co.in

Formerly : Meditronics sales & services pvt. ltd.

Authorised Representative



NOTE : specification subject to change without prior notice

## Biphasic Monitor-Defibrillator

Defibrillator + ECG + SPO<sub>2</sub> (optional) + NIBP (optional)  
+ Pacemaker (optional) + AED (optional)

New CardioMax biphasic monitor defibrillator line: a new medical equipment generation with the highest technology.

Cardiomax represents a new level to the sector. Advanced characteristics of versatility, ergonomics, design, mobility and easy-use, makes it the biggest package of advantages in only one device.

And, being a Medion product, you know: it has the better cost-benefit, guarantee of total technical support and can be configured exactly as your needs.



**More versatility: multifunctional paddles, adults and pediatric, easy to use. Integrated in one piece, with bargraph, displays the contact with skin and buttons of shock and charge.**

**Cardiomax: a new equipment generation developed for the highest requirements of technology, quality and functionality.**



- Modern design, robust and intelligent, ideal for hard emergency removals.
- Lightweight – only 6 kg (with battery and paddles), small and compact, with designed handle for transport.
- Fast and easy battery changing, without opening the equipment.
- 60 shocks delivery

- Active matrix color display with and perfect ample visualization of all the information and waveforms.
- Easy operation – 1, 2, 3 pattern.
- Biphasic shock in up to 360 joules, ECG and SpO<sub>2</sub> (optional), NIBP (optional), external pacemaker (optional) and cardioversion.
- Recorder (inbuilt).

CARDIOMAX



**A new generation of interfaces: clean, elegant and intuitive, that offers an intelligent and dynamic visualization allowing the fastest interpretation.**