

PIPE EQUIPMENT SPECIALISTS LTD

PREP 4 PIPE BEVELLING 1" to 4"









RANGE: 23 to 112mm i/d

Functions: External Bevelling

Internal Bevelling Elbow Bevelling

Facing

Counter-boring Weld Removal

J-Prepping and facing of Tubeplate

Materials: Any kind of Steel

and Exotic Alloy

Power: Pneumatic / Electric / Battery

(110v or 220v)

The PREP 4 is one of our most popular i/d locking, in-line feed end prep machines. The PREP 4's power to weight ratio, in electric, battery (110v or 220v), or pneumatic drive form is unrivalled.

A 4 jaw tool holder (chuck) allows use of up to 4 insert or form tools to enable bevelling of heavy wall pipe & tube, simultaneous external, internal and facing of tubes can be performed with ease for accurate repetitive work.

Its size, power, and functionality, makes it extremely popular in high volume boiler repair and maintenance work, tube facing, weld removal, and J-prepping of the tube plate.



The PREP 4 is torque reactive. This means that the pipe or tube does not have to be fixed to be beveled, making it particularly useful on-site, in maintenance and repair situations. This is due to the design and strength of the thru shaft system that locks to the bore of the pipe.

The Jaw system itself consists of 3 equilaterally positioned machined jaw segments, retained and locked on an inner, 'grooved' expansion shaft.

These grooves keep the jaws held securely in position, unlike other systems that use a metal or rubber bands for jaw retention.

As the expansion nut is is tightened, the jaws expand, locking tightly, and square to the bore of the pipe.





000


CE







POWER OPTIONS:







ACCESSORIES & OPTIONS:
















PREP 4 TECHNICAL FEATURES:

DESCRIPTION	MEASUREMENT	PNEUMATIC	ELECTRIC	BATTERY
Part Number	-	TP4P	TP4E	TP4B
Locking tube range	mm (i/d.)	23 - 112	23 - 112	23 - 112
Recommended working range	inch (o/d.)	1 - 4"	1 - 4"	1 - 4"
Idle speed	rpm	0 - 100	5 - 82	55
Torque	kgm/nm	14.1 / 138+	19.7 / 193+	22.1 / 216+
Length of axial feed	mm	40.5	40.5	40.5
Max operating temperature	c°	55	55	55
Max acoustic radiation	dB	75	75	75
Pneumatic motor power	hp	1.5	-	-
Air consumption	cfm	34 - 36	-	-
Air working pressure	psi	90	-	-
Air hose connection	inches	3/4"	-	-
Electric motor power	watt	-	1300	1800
Voltage	volt	-	110 / 220	charger 110 / 220
Frequency	Hz	-	50 / 60	charger 50 / 60
Unit weight	kg	9.4	10.4	11.1
Packing dimensions	mm	640 x 500 x 140	640 x 500 x 140	640 x 500 x 140
Packing weight	kg	28.5	29.5	30.5

All units are supplied complete with all locking jaws to cover the full range of the machine. Service tools, drawings, instruction manual and warranty certificate and protective metal carrying case.

DIMENSIONS ⋖ DIM **PNEUMATIC ELECTRIC BATTERY** Α 455mm 510mm 540mm В 434mm 434mm 434mm С 140mm 140mm 140mm D 115mm 115mm 115mm 60mm Ε 90mm 90mm







PIPE EQUIPMENT SPECIALISTS LTD PRODUCTS INCLUDE:

PIPE BEVELLING MACHINES

















TAG Head Office

TAG PIPE EQUIPMENT SPECIALISTS LTD
Unit 15 & 16 Grendon Industrial Estate, Grendon Underwood,
Aylesbury, Buckinghamshire, HP18 OQX England
Tel: +44 (0)1869 324 144 E-mail: sales@tag-pipe.com

www.TAG-PIPE.com

Overseas Branches



USA Branch

TAG PIPE EQUIPMENT SPECIALISTS INC 527 Michigan Street, South Houston Houston, Texas 77587, USA Tel: +1 713 660 1427 E-mail: sales-usa@tag-pipe.com



Europe Branch

TAG PIPE EQUIPMENT SPECIALISTS BVBA
Mosten 13, 9160 Lokeren
Belgium
Tel: +32 486 46 62 93

E-mail: sales-europe@tag-pipe.com



Middle East Branch

TAG PIPE EQUIPMENT SPECIALISTS FZE
Al Ittihad Street, P.O. Box 3763
Dubai, United Arab Emirates
Tel: +971 (0)50 680 3107
E-mail: sales-me@tag-pipe.com



India Branch

TAG PIPE EQUIPMENT SPECIALISTS PVT
Plot No. PAP 3, D 3 Block,
Chinchwad, Pune 411 019
Tel: +91 20 6573 4333
E-mail: sales-india@tae-pipe.com



Asia Branch

TAG PIPE EQUIPMENT SPECIALISTS PTE
Yinhe Bridge West, Beichen District
Tianjin, China
Tel: +86 139 2001 5417
E-mail: sales-asia@tae-pipe.com