Language English	STRATOS STAIR	LIFT	Date		
	ORDER FORM	М	Version	STRATOS.LE.20	
	Distributor: (always fill out)	Delivery addr	ess: (always fill out)		
	Company	Company			
LEHNER Differentik	Address	Address			
	Postcode	Postcode			
Salling 8	City	City			
4724 Neukirchen am Walde	Country	Country			
Austria	Telephone Email	Telephone			
Production no.	Order referer	nce name (or number)			
Rail specification	<u></u>				
Installation location		Indoor			
Installation side		Right			
Rail length in meters rounded					
Lower stop	Straight				
Upper stop	Straight at last step				
Number of 90° curves					
Number of special curves					
Horizontal drive (inclination <20°)		No			
Length of horizontal rail in meters					
Number of vertical bends					
Number of intermediate stops					

General platform specifications Excecution Folding seat Loading capacity

Platform dimension Folding mechanism Loading ramps

Front folding ramp 85 degree

Ramps length
Ramps surface
Carriage control version
External landing controls (always rad

External landing controls (always radio) Removing key in ON position

Safety features acc. to EN 81-40

Lateral safety pads
Overload signal
Visual signal (bespek

Visual signal (bespoke solution)

$\underline{\textbf{Further specifications}}$

Plastic cover for outdoor stairlift
Padlock against unfolding of the platform
Transport box

Surface treatment

Platform and carriage Rail and brackets

Supporting structure

Fixing of the rails
Arrangement of pillars
Adjusting slots on pillars

Platform + rail (standard)					
Without folding seat					
225 kg					
800 x 1000mm					
Automatic (standard)					
Upper and lower ramp					
No (standard)					
200mm (standard)					
Same colour as platform					
All commands on controls on spiral cable (standard)					
Membrane keypad (standard)					
No (standard)					

Yes
Yes
No

No
No (standard)
Q1

RAL 7035 (standard)
RAL 7035 (standard)
RAL 7035 (standard)

On the pillars only On the steps (standard) Yes

Additional information

<u> </u>				1	
Delivery date	Week	-	2019	Prepared by	