

MFT 4000 D High Capacity Trailer Fire Pumps



Flood Relief | Fire Fighting | De-watering













APPLICATIONS

- De-Watering
- Fire Fighting
- Flood Relief
- De-Watering of Cellar Pits
- Industrial Washing

SECTORS

- Oil Refineries
- Smart Cities
- Paper Industries
- Cotton Mills
- Chemical Industries
- Sugar Mills
- Warehouses

The Trailer mounted pump can be used as a heavy duty fire pump and for a wide range of performances that requires the benefits of firefighting with the ability to move large volumes of water continuously. The design has been specifically developed to meet the needs of the emergency services around a large site and incorporates features to ensure easy and reliable operation in fire and flood rescue situations.

Electric start, fully equipped Control panel and highly reliable priming System mean the pump can be put into service quickly and easily in an emergency situation by one person.



Salient Features of MFT 4000 D

- Performance 2270 Litre/minute at 7 bar for fire fighting operations and 4000 Liters/minute at 3 bar for flood rescue operations
- Supplied with reputed make variable speed engine
- Priming system Two types of Priming System provided capable of lifting the water from 7 meter suction height within 36 seconds with 140 mm suction hose
- ▶ Fuel Tank Capacity 65 litres
- Material of Pump Aluminium / Gunmetal / Stainless Steel
- ▶ Easy push button type electric start & emergency stop
- ▶ Completely illuminated control panel & Flood lamp for night operations
- Can be towed by any vehicle
- Adequate ground clearance to tackle speed breakers, flooded road and independent suspension for improved handling
- Stabilizer jacks for added safety during operation

Technical Specifications

MODEL	MFT 4000 D
Pump type	Single stage centrifugal fire pump
Rated Performances	2270 LPM at 7 bar
	4000 LPM at 3 bar
Engine	4 cylinder 4 stroke naturally aspirated water cooled diesel engine
Fuel tank capacity	65 litres
Suction Inlet	140 mm single inlet with British standard round threads
Delivery Outlet	4 delivery outlets fitted with 63 mm instantaneous couplings
Dimensions (L x W x H)	L - 3200 mm x W - 1600 mm x H - 1700 mm
Weight	Not more than 1200 kg.





