


TECHNICAL CHARACTERISTICS

- 1) MAX. WORKING VOLTAGE : 415 / 500 V.A.C. 50 C/S
- 2) MAX. CURRENT RATING : 40 AMPS. (MAX.)
- 3) GEAR RATIO:- 48 : 1 OR 60 : 1 , 96:1
- 4) MAX. PERMISSIBLE NO. OF REVOLUTIONS : 40 OR 50 , 80
- 5) MAX. NO. OF CONTACTS
FOR TWO WAY SHUNT TYPE- 2 NOS (2 N.C.)
- 6) ENCLOSURE :- IP 54 CONFORMING TO IS /IEC 60529 : 2001

TYPE

- A - Suni/RLS/48/2SH/2
- B - Suni /RLS/60/2SH/2

**SECTION A-A
INPUT SHAFT**

 Suni® Cranes Controls AN ISO 9001:2015 CERTIFIED COMPANY		सनी क्रेन्स कन्ट्रोलस एन आय.एस.ओ.९००१:२०१५ सर्टीफाईड कम्पनी		
Shubh Indl. Estate Vasai(E) PALGHAR-401208				
ALL DIMENSIONS ARE IN MM.		TOL — OVERALL DIM ±5MM. BOLTING CENTER ±3MM.		
TITLE. ROTARY GEAR LIMIT SWITCH				
DRN.	PRAKASH	27/03/16	SCALE	N.T.S.
CHD.	G.G.YADAV	27/03/16	MATL.	ALUMINUM
APPD.	G.G.YADAV	27/03/16	TYPE NO. Suni/RLS2SH2	
DRG. NO.	Suni / GA / RLS/03			REV — 0