

High Speed Centrifuge IG-70BL



Address: 16/2 | Ground Floor | Ashok Nagar | New Delhi-110018 |

Office: - 011-79613060| Email: info@igenels.com| Web: www.igenels.com



Features

- Brushless motor with simple construction, more reliable performance, longer life and noise less run.
- Microprocessor control, digital indicator for speed, temperature and time, running parameters can be edited and changed to RCF.
- Heavy duty C.R.C. construction finished with powder coating Stainless Steel centrifugal bowl for extra protection and easy cleaning.
- Fitted with well-balanced brushless motor with electronic drive.
- Digital timer 0-99 minutes. 4 lines 20 characters LCD display for set time, run time, set & run rpm, rcf and rotor identification.
- 50 programmes can be stored in memory and automatic rotor identification on display.
- Additional electronic lid lock who does not allow opening lid when machine is running and opens automatically after centrifuge time is over.
- Dynamic brake (automatic) and imbalance detector are provided.
- Fast spin option. Selection of 3 acceleration + 4 deceleration profile.
- Programmable Speed Regulator from 2000 to 20000 in interval of 100 rpm
- Last test parameter recall and displays automatically on LCD
- Supply with instruction manual, cord & plug to work on 220 volts 50Hz A.C.

Specifications

Max speed	20000rpm	Max RCF	27800xg
Max volume	4x100ml	Temp Range	-20 °C to RT
Timer	1 ~ 99min	Working/Standby Temp	-8°C/-20° C
Dimension(HxDxW)	381X685X534mm	Net weight	50KG
Speed accuracy	±20rpm	Power supply	AC 220V 50HZ 10A

Order No.	Rotor	Max speed(rpm)	Max capacity	Max RCF(xg)
L70B-4000	Angle rotor	13000	4*100ml	16270
L70B-1215	Angle rotor	20000	12x1.5/2.0ml	27800
L70B-2402	Angle rotor	16000	24*1.5/2ml	22240
L70B-0650	Angle rotor	13000	6x50ml	19155
L70B-0815	Angle Rotor	13000	8x15ml	19155

Address: 16/2 |Ground Floor| Ashok Nagar| New Delhi-110018|

Office: - 011-79613060| Email: info@igenels.com| Web: www.igenels.com

