



## AKERO- 120i-6

### FULLY AUTOMATED CLINICAL CHEMISTRY ANALYSER

### TECHNICAL SPECIFICATIONS

9

Item	Description
Throughput	<ul style="list-style-type: none"> <li>• 120 test/hour</li> </ul>
System type	<ul style="list-style-type: none"> <li>• Discrete, open/ closed (Optional), fully automated</li> </ul>
Sample	<ul style="list-style-type: none"> <li>• Serum, Urine, Plasma, CSF, Other body fluids</li> </ul>
Measurement principle	<ul style="list-style-type: none"> <li>• Photometric and HIAS (Homogeneous Immuno Assays)</li> </ul>
Wavelengths	<ul style="list-style-type: none"> <li>• 9: 340,405,450,510,546,578,620,660,690nm</li> </ul>
Photometer Linearity	<ul style="list-style-type: none"> <li>• Up to ±3.0 Optical Density</li> </ul>
Light source	<ul style="list-style-type: none"> <li>• Tungsten halogen lamp (12V 20 W)</li> </ul>
Programmable parameters	<ul style="list-style-type: none"> <li>• 50 photometric tests</li> </ul>
Assay modes	<ul style="list-style-type: none"> <li>• End Point, Fixed time, Rate-A, RateB, MultiPoint Non Linear</li> </ul>
Sample positions	<ul style="list-style-type: none"> <li>• 25 for standard cups/ primary tubes/ STAT</li> </ul>
Sample volume	<ul style="list-style-type: none"> <li>• 2-50 µl (adjustable in 0.1 µl step)</li> </ul>
STAT Sampling	<ul style="list-style-type: none"> <li>• STAT sampling at any position</li> </ul>
Reagent positions	<ul style="list-style-type: none"> <li>• 25 for combination of 18mL and 5mL bottle size</li> </ul>
Reagent volume	<ul style="list-style-type: none"> <li>• 10 – 300 µl (adjustable in 1 µl step)</li> </ul>
Reagent cooling	<ul style="list-style-type: none"> <li>• 15°C below ambient room temperature (approx 25°C)</li> </ul>
Reaction volume	<ul style="list-style-type: none"> <li>• 150µl to 300µl</li> </ul>
Level sensing and safety mechanism	<ul style="list-style-type: none"> <li>• Vertical obstruction detection</li> <li>• Inventory management by Capacitance based sensing</li> </ul>
Reaction temperature	<ul style="list-style-type: none"> <li>• 37 °C± 0.2 °C</li> </ul>
Calibration	<ul style="list-style-type: none"> <li>• Max 6 calibrators per test with Calibrator auto-dilution</li> </ul>
Calibration curves	<ul style="list-style-type: none"> <li>• K-Factor, Linear (one, two and multipoint), Logit-log (4P and 5P), Spline, Exponential and Polynomial</li> </ul>
Quality control	<ul style="list-style-type: none"> <li>• Tri level Daily and Monthly L J Graphs with Multi QC Rules</li> </ul>
Mixing type	<ul style="list-style-type: none"> <li>• By paddle mixer with variable speed (Low/ Middle/ High)</li> </ul>
Sample dilution	<ul style="list-style-type: none"> <li>• Pre/Post dilution for &gt;Linearity &amp; Substrate Depletion</li> </ul>
Sample and reagent tray	<ul style="list-style-type: none"> <li>• Rotating turn table with insulating cover</li> </ul>
Sample/Reagent Identification	<ul style="list-style-type: none"> <li>• Positive Identification (barcoding) for samples&amp; reagents</li> </ul>
Cuvette washing	<ul style="list-style-type: none"> <li>• 7 stages cuvette washing with drier chip</li> </ul>
Data storage capacity	<ul style="list-style-type: none"> <li>• Test results: 1,000,000, Reaction curve: 40,000 tests</li> </ul>
Graph monitoring	<ul style="list-style-type: none"> <li>• Online for Reaction and Calibration curve</li> </ul>
Water consumption	<ul style="list-style-type: none"> <li>• NCCLS Type II, 4.0 liters/hour (approx)</li> </ul>
Noise level	<ul style="list-style-type: none"> <li>• Less than 65 dB with cover closed</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• Approximately 40Kgs</li> </ul>



Marketed By:  
**Melrose Healthcare Pvt.Ltd.**,  
 Block-B 36/37,Millennium House,  
 M.K.Srinivasan Nagar,Main Road,  
 Perungudi,Chennai-96  
 Ph: (M) +91 9840238373  
 E-mail : melrosetechcare@hotmail.com  
 Website : www.melrosehealthcare.com

In Association with Akero Sekai Ichii Incorporation

