

• Recess - Diffuser Down light




80 CRI

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance recess luminaire
- The complete luminaire is made of CRCA sheet steel
- Highly efficient passive cooling deep drawn housing
- High efficiency polycarbonate symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) led mounted on MCPCB for better thermal performance
- Isolated - high efficiency electronic driver fitted on the luminaire
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated-white, black


Available Colours



IP 20 White Black Wide

TECHNICAL SPECIFICATIONS

Light Source	: MPL - Mid Power Led
Power Consumption	: 24W, 30W, 36W
Color Temperature	: 3000 K 4000 K 6500 K
Lumens	24W : 1923 lm, 2066 lm, 2420 lm 30W : 2684 lm, 2714 lm, 2885lm 36W : 3180 lm, 3230 lm, 3390 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 270 V
Output voltage	: 24V - 36V DC
Output Current	: 650 mA 800 mA 1000 mA
Power Factor	: >0.98
THD	: <15%



All dimensions are in mm

Product Application :
Retail Space | Ambient | Trial Room | Stair case