

• Pendant mount - Down light



80 CRI

## PRODUCT HIGHLIGHTS

- Aesthetically designed trunking mounted luminaire
- Luminaire housing made from high-grade extruded aluminum
- High efficiency passive cooling technology for good thermal management
- Aesthetically designed micro prismatic wing shape high efficiency pc symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) LED technology used in FR-4 PCB/MCPCB based on the wattage selection
- Isolated-high efficiency electronic driver mounted on the luminaire
- Complete luminaire is enclosed with abs-end cap
- Sliding clocking system-to suite trunking mounting
- Shade : powder coated-white, black



## TECHNICAL SPECIFICATIONS

Light Source	: MPL- Mid Power LED
Power Consumption	: 20w, 25w, 32w, 36w, 44w, 48w, 52w, 54w
Color Temperature	: 4000 K   5700 K   6500 K
Lumen	20W : 2321 lm, 2343 lm, 2428 lm
	25W : 2772 lm, 2829 lm, 2882 lm
	32W : 3456 lm, 3504 lm, 3552 lm
	36W : 4032 lm, 4080 lm, 4128 lm
	44W : 4512 lm, 4560 lm, 4608 lm
	48W : 4992 lm, 5042 lm, 5088 lm
Lumen	52W : 5184 lm, 5232 lm, 5280 lm
	54W : 5664 lm, 5712 lm, 5760 lm
	54W : 5664 lm, 5712 lm, 5760 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 240 V
Output voltage	: 47V - 51V DC
Output Current	: 200 mA   250 mA   300 mA   350 mA
	: 800 mA   900 mA   950 mA   1050 mA
Power Factor	: >0.98
THD	: <10%



All dimensions are in mm

**Product Application :**  
Retail Space | Hyper & SuperMarket