


Orient XLC :
30,000 CPH

Orient XLC

Orient XLC is a single width Single circumference web-offset press with a speed up-to 30000 copies per hour for high quality newspaper printing, tabloid printing, book printing and commercial products.

This machine provides a compact alternative to traditional web-offset presses and is one of the most technologically advanced presses in the market today with an excellent ROI for our patrons.



XLC - 30,000 specifications

Printing speed – 30,000
cph

Paper width – 660 to
889mm
Motorized ink fountain
roller

Motorized two RCR's (+/-
1.5mm) on each stack
Motorized two Side Lay
(+/-3mm) on each stack

One no. ink vibrator roller
(each side)

Web wrap contact instead
of line contact between
blanket to blanket to
prevent fluttering of web.

Pneumatic on – off
controls

Variable speed motorized
Contactless brushmist
dampening system.

Each 2-Hi in one frame
only (operating side &
drive side)

XLC - 30,000 specifications

- Compact 4-Hi tower. Without top link height is at only 3065mm
- Compact Width of 4-Hi tower at only 1390mm
- Bearers on plate & blanket cylinders
- Slit type plate lockup
- Narrow gap type blanket cylinders
- Timer belt drive between lower & upper 2-Hi only
- One extra rider roller on each side
- Hardened and ground bushes in plate & blanket cylinder bores.



Quality Standards

- TPH is an **ISO 9001:2008** company
- TPH also has certification

OHSAS 18001:2007

for health and safety Management System.

&

ISO 14001:2004

for Environmental Management System.

- Over **3,000** quality checks are conducted for optimum performance

TECHNICAL SPECIFICATION X- CEL PLUS

S.NO	PARTICULARS	CUT-OFF 578
1	SPEED	30000 cph
2	PAPER WIDTH FULL REEL	660 – 889 mm
3	MAX REEL DIA	1070 mm
4	PLATE WIDTH	889 mm
5	PLATE LENGTH SLIT TYPE	609 mm
6	BLANKET WIDTH	889 mm
7	BLANKET LENGTH (NARROW GAP)	651 mm
8	BLANKET THICKNESS/ WITH PACKING	1.70/2.1 mm
9	PRINTING LENGTH (NARROW GAP)	563 mm
10	PLATE THICKNESS	0.28 mm
11	PAPER GRAMMAGE (UNCOATED)	38-100gm/s.q.m