

Multi-Use PDF TEMP&RH Data Logger

Multi-Use PDF TEMP&RH Data Logger is the perfect tool for cold-chain monitoring and documentation of temperature and relative humidity conditions that are critical in laboratories, pharmaceutical, medical, storage, freezers, coolers, shipping containers, warehouses, environmental monitoring and food storage applications.



Features:


- *Designed to be Multi-use
- *Temperature & Humidity measurement and recording
- *Statistics available on LCD screen
- *No software needed to export data
- *Automatically generates PDF report and CSV file
- *Reprogrammable software for logging parameters, alarms, and start delay




Specifications:

Temperature Scale	°C or °F
Accuracy	±3%RH; ±0.5°C (-20°C ~ +40°C), ±1.0°C(other range)
Measurement Range	Humidity 0%~100%RH, Temp -30°C ~ 60 °C
Resolution	0.1%RH typically 0.1°C
Memory Capacity	32,000
Recording Options	Delayed or Push-To-Start Logging
Record Interval	10 seconds to 18 hours adjustable [Default:10 mins]
Start Delay	Start Delay Programmable (0 ~ 254 mins) [Default: 30 mins]
Alarm Delay	Programmable (0 ~ 960 mins) [Default: 10 mins]
Alarm Range	Programmable high or low alarm limit for each channel [Default: <2°C or >8°C, <40%RH or >80%RH]
Shelf Life / Battery	Typically 1 Year; CR2032 3.0V Lithium Battery (Depending on Sampling Rate and Environment)
Report Generation	Simultaneously generate PDF report and CSV file
Communication Interface	USB2.0
Time Zone	UTC +0:00 (Default)
Demensions	89mm x 36mmx 16mm
N.W.	25g


How to use:



press the button to start



put into the box / carton



logging goods TEMP&RH



connect PC to get PDF Report & CSV file