



THREE LUG TYPE FILTER CARTRIDGE.



❖ CONSTRUCTION

- These are made with 100% spun bonded polyester filter fabrics with GI/SS/PP Filter Cage as core inner retainer material.
- **Aluminium** three lug type top cap and metal end(bottom) cap.
- Also use the stripes for pleats support.

❖ TECHNICAL SPECIFICATION

- SIZE : - 1. DIAMETER: 140mm
PCD: 174mm
ID : 83mm
- 2. DIAMETER : 150mm
PCD: 209mm
ID : 85mm
- 3. DIAMETER : 225mm
PCD: 266mm
ID : 110mm
- 4. DIAMETER : 325mm
PCD: 393mm
ID : 206mm

- **Size :- 140/150/225/325 mm diameter.**
- **Length :- 500/1000/1500 mm long.**
- **Filtration Rating: - 0.96 – 25 micron**
- **Outside Diameter: - 145 – 150 mm**
- **Filtration area: 1 – 5.5 SQM maximum**
 - **Media configuration available:**
- Spun bonded polyester –plain fabric
- Spun bonded polyester –Oil and Water repellent (OWR)
- Spun bonded polyester –PTFE coated
- Spun bonded polyester –Aluminium anti static coated
- Spun bonded polyester –ePTFE membrane laminated

❖ FEATURES

- Very Economical
- Very Strong outer Cage.
- Temperature: Ambient
- Open Pleat Spacing.
- Low consumption of compressed air (for cleaning).