
ARO

Pumps for the Construction and Mining Industries



INGERSOLL-RAND FLUID PRODUCTS

Air-Powered Submersible Pumps

For water removal on Construction and Mining Sites

Water on site or down the hole?

Need a submersible pump that can cope with mud, leaves, twigs, bilge, gunk and even sewage? The answer is the Ingersoll-Rand/Aro range of sump pumps.

Running on compressed air means there's no fuel tanks, electrical connections or burnt out motors to worry about.


Despite their compact size and light weight, their ultra-rugged construction can take plenty of abuse and still discharge over 750 l/min.

Try one on your toughest job and just see what a real pump can do.

- Simple design few moving parts
- Handles a wide variety of debris-laden applications
- Can also be used for simple transfer requiring high flows (750 l/min. average) with high discharge head (20 metres average)
- Self-priming
- Adjustable Impeller and Impeller Cover help maintain peak performance
- Closed-type Impeller promotes greater efficiency when pumping against high heads
- Ultra-rugged body construction ensures durability
- Lightweight and extremely portable
- Pressurised lubrication of the Impeller Shaft Seals prolongs operational life and resists leakage
- Patented Speed Controller is guaranteed for the life of the pump
- Totally submersible

TYPICAL APPLICATIONS

- Mining
- Construction
- Plant Machine Sumps



Specifications at 620 kPa air pressure.

Model	Pump housing material		harge ap size	Weight	Height	Air consumption	Size of opening pump will	Ai Pipe tap	ir inlet Size hose recom-		xhaust Size hose recom-
	materiai	NPT	BSP				pass through	size	mended	size	mended
		in	in	kg	mm	l/sec.	mm x mm	in	mm	in	mm
P237A1-EU	Iron	2½	-	21.8	448	50	222 x 222	3/4	19	11/4	32
P237A3-EU	Iron	-	21/2	21.8	448	50	222 x 222	3/4	19	11/4	32
P35A1-EU	Iron	2	-	36.0	570	75	214 x 357	1	25	11/4	32
P35A3-EU	Iron	-	2	36.0	570	75	214 x 357	1	25	11/4	32

See Page 6 for Accessories and Service Kits



Air-Powered Pumps

For water removal on Construction and Mining Sites

Known throughout industry as the "Unstallables", Ingersoll-Rand/Aro Diaphragm pumps have long been favourites with fluid handling professionals for their patented no-stall and ice-free operation, as well as a host of other design attributes.

To increase the range of applications, pre-assembled screen inlet pumps and retrofittable inlet kits are available to help tackle problems with unwanted and unavoidable debris.

- Stall-free, ice-free, debris-free fluid handling
- Available complete with screen or with extra retrofit screen kit
- Tough metallic construction in aluminium with stainless steel fasteners
- Screens constructed in carbon steel with e-coat finish
- No special manifold required screen comes ready installed on pump making it ready for immediate service

TYPICAL APPLICATIONS

- Construction
- Mining
- Chemical Process
- Industrial Maintenance
- Marine

Specifications at 620 kPa air pressure.



PS20A-AAS-AAA









PS30A-AAS-AAA

					exhaust	imet/outlet	consumption	max. Ø
(g			ltr/min.				l/sec.	mm
24	Aluminium	Ball	379	½" NPT	½" NPT	1½" NPT	65	6.4
24	Aluminium	Ball	379	½" BSP	½" BSP	1½" BSP	65	6.4
30	Aluminium	Ball	644	¾" NPT	¾" NPT	2" NPT	70	6.4
30	Aluminium	Ball	644	¾" BSP	¾" BSP	2" BSP	70	6.4
52	Aluminium	Ball	1041	¾" NPT	¾" NPT	3" NPT	80	9.5
52	Aluminium	Ball	1041	¾" BSP	¾" BSP	3" BSP	80	9.5
LET								
23	Aluminium	Ball	379	½" NPT	1½" NPT	1½" NPT	65	6.4
23	Aluminium	Ball	379	½" BSP	1½" BSP	1½" BSP	65	6.4
29	Aluminium	Ball	644	¾" NPT	1½" NPT	2" NPT	70	6.4
29	Aluminium	Ball	644	¾" BSP	1½" BSP	2" BSP	70	6.4
51	Aluminium	Ball	1041	¾" NPT	1½" NPT	3" NPT	80	9.5
51	Aluminium	Ball	1041	¾" BSP	1½" BSP	3" BSP	80	9.5
	24 4 4 60 60 60 62 62 62 LET 33 33 89 99 61	Aluminium	Aluminium Ball	24 Aluminium Ball 379 24 Aluminium Ball 379 26 Aluminium Ball 644 26 Aluminium Ball 1041 22 Aluminium Ball 1041 22 Aluminium Ball 379 23 Aluminium Ball 379 29 Aluminium Ball 644 29 Aluminium Ball 644 31 Aluminium Ball 644 31 Aluminium Ball 1041	24 Aluminium Ball 379 ½" NPT 24 Aluminium Ball 379 ½" BSP 20 Aluminium Ball 644 ¾" NPT 30 Aluminium Ball 644 ¾" NPT 30 Aluminium Ball 1041 ¾" NPT 32 Aluminium Ball 1041 ¾" BSP LET 33 Aluminium Ball 379 ½" NPT 33 Aluminium Ball 379 ½" BSP 49 Aluminium Ball 644 ¾" NPT 49 Aluminium Ball 644 ¾" BSP 51 Aluminium Ball 1041 ¾" NPT	24 Aluminium Ball 379 ½" NPT ½" NPT 24 Aluminium Ball 379 ½" BSP ½" BSP 26 Aluminium Ball 644 ¾" NPT ¾" NPT 30 Aluminium Ball 644 ¾" BSP ¾" BSP 32 Aluminium Ball 1041 ¾" NPT ¾" NPT 32 Aluminium Ball 1041 ¾" BSP ¾" BSP 4 BSP ¾" NPT 1½" NPT 1½" NPT 43 Aluminium Ball 379 ½" NPT 1½" BSP 49 Aluminium Ball 644 ¾" NPT 1½" NPT 49 Aluminium Ball 644 ¾" BSP 1½" BSP 51 Aluminium Ball 1041 ¾" NPT 1½" NPT	24 Aluminium Ball 379 ½" NPT ½" NPT 1½" NPT 24 Aluminium Ball 379 ½" BSP ½" BSP 1½" BSP 24 Aluminium Ball 644 ¾" NPT ¾" NPT 2" NPT 30 Aluminium Ball 644 ¾" BSP ¾" BSP 2" BSP 32 Aluminium Ball 1041 ¾" NPT ¾" NPT 3" NPT 42 Aluminium Ball 1041 ¾" BSP ¾" BSP 3" BSP 42 Aluminium Ball 379 ½" NPT 1½" NPT 1½" NPT 43 Aluminium Ball 379 ½" BSP 1½" BSP 1½" BSP 49 Aluminium Ball 644 ¾" NPT 1½" NPT 2" NPT 49 Aluminium Ball 644 ¾" BSP 1½" BSP 2" BSP 51 Aluminium Ball 1041 ¾" NPT 1½" NPT 1½" NPT	Aluminium Ball 379 ½" NPT ½" NPT 1½" NPT 65 Aluminium Ball 379 ½" BSP ½" BSP 1½" BSP 65 Aluminium Ball 644 ¾" NPT ½" NPT 70 Aluminium Ball 644 ¾" NPT ½" NPT 3" NPT 80 Aluminium Ball 1041 ¾" NPT ¾" NPT 3" NPT 80 Aluminium Ball 1041 ¾" BSP ¾" BSP 3" BSP 80 LET Aluminium Ball 379 ½" NPT 1½" NPT 1½" NPT 65 Aluminium Ball 379 ½" BSP 1½" BSP 65 Aluminium Ball 379 ½" BSP 1½" BSP 65 Aluminium Ball 644 ¾" NPT 1½" NPT 2" NPT 70 Aluminium Ball 644 ¾" NPT 1½" NPT 2" NPT 70 Aluminium Ball 644 ¾" BSP 1½" BSP 70 Aluminium Ball 644 ¾" BSP 1½" BSP 2" BSP 70 Aluminium Ball 644 ¾" BSP 1½" BSP 2" BSP 70 Aluminium Ball 644 ¾" BSP 1½" BSP 2" BSP 70 Aluminium Ball 644 ¾" NPT 1½" NPT 3" NPT 80

See Page 6 for Accessories and Service Kits



Air-Powered Lubrication Pump Packages

For Construction, Maintenance and Heavy Duty Lubrication

Need to oil or grease your machinery? We have powerful stall-free, ice-free answers!



Gear Oil, 5:1 Ratio, 3" Diameter Air Motor

60 litre (16 U.S. gallons) Portable Gear Oil Package

Includes:

LM2305A-31 Basic Pump, 635190-3 Meter 635391-1 (flex) Control Handle, 640058-2 Dolly, 94421 Drum Cover 623501-6 Material Hose (1.8m).

Model No.

LP3100-2



ARO-PAK® Self-Contained Lubricators

Holds 2.3kg (5lbs) medium pressure lubricant and 40 PSI air prime for portability. Air pressure helps dispense lubricant.

1.2m of $\frac{1}{2}$ " I.D. hose. High pressure control handle (517 bar).

Model No.

640110



54kg (120lbs) Filler Pump


2:1, 4:1, 7:1 Adjustable Ratio Used to fill grease gun and 640110 ARO • PAK Includes:

72096 Drum Cover, Dust Cap

(640027 Follower Plate not included - order separately)

Model No.

611019-1



IMPORTANT

The 50:1 ratio grease packages listed have a maximum air inlet pressure of 10 bar

See Page 7 for Accessories and Service Kits



Grease, 50:1 Ratio, 3" Diameter Air Motor

18kg (35lbs) Grease Package

Includes:

LM2350E-21-B Pump 94420 Drum Cover with 94334 Handle 640095-2-B Follower Plate 624201-10 Material Hose (3m), 636077 Z-Swivel 76493 Adapter 636103 Booster Gun

Model No.

LP3001-1



27kg (60lbs) Grease Package

Includes:

LM2350E-61-B Pump 71740-1 Drum with Cover and Tie Down Brackets Portable Hand Cart 636111 Control handle 624401-4 Material Hose (1.2m).

Model No.

LP3007-1



54kg (120lbs) Grease Package

Includes:

LM2350E-31-B Pump

94421 Cover

624201-10 Material Hose (3m),

636077 Z-Swivel

640057 Dolly

636103 Booster Gun

640165 Follower Plate

76493 Adapter.

Model No.

LP3003-1



181kg (400lbs) Grease Package Includes:

LM2305A-41-B Pump 94422 Drum Cover 624401-4 Material Hose (1.2m) 622201-3 Air Line Hose (0.9m) Order Follower Plate 640015 - when required.

Model No.

LP3005-1

Air-powered High Pressure Cleaning Equipment

Time to clean up your act? We've got the power!

Spray Wash Pump Packages







Mounted Spray Package Includes: 613100-1 Pump

41/4" High Pressure Wall-

613100-1 Pump 61113 Wall Bracket 61139-1 208 litre Suction Tube Assembly 622427-40 Material Hose (12m) 641523 Control Handle 61133 Spray Wand TP6250-18 Spray Tip L26241-010 Airline Lubricator.

Model No.

613104

8" High Pressure Wall-Mounted Spray Package

Includes:

613112-K36-B Pump
92460 Muffler
66554-3 Heavy Duty Cart
622702-10 Suction Hose (3m)
79198 Stainless Steel Inlet Strainer
79196 Material Outlet Manifold
622427-40 Material Hose (12m)
641523 Control Handle
61133-1 Spray Wand
TP8050-18 Spray Tip
651728 Heavy-Duty Air Filter
Regulator
Lubricator

Model No.

613117-B

The High-Power Cleaning Solution

Perfect for cleaning:

- Cars and Trucks
- Engines
- Construction Equipment
- Aircraft

- Farm Equipment
- Plant Structures
- Railway Equipment
- Fleet Vehicles
- Mining Equipment

With the application of:

- Degreasers
- Detergents
- Cleaning Solutions
- Water

- Metal Brighteners
- Aluminium Brighteners

Calcium Chloride Tyre-Fill Pump Package



Designed for the purpose of evacuating and filling tyres with calcium chloride ballast solution.

Package includes:

666100-441-C, 1" Ports Diaphragm Pump. (aluminium construction with neoprene diaphragms and Teflon* checks for compatibility with corrosive calcium chloride) 60154 Hose/Strainer/Gun Assembly Also includes Check Valve and all required clamps and related hardware.

See Page 7 for Accessories and Service Kits

Model No.

613201-2-C

Having trouble staying on the ground?

We'll keep you down to earth!



Accessories and Service Kits **Pumps**

Looking for pumping equipment to dry out your site? We're the single source supplier for all your needs!

Centrifugal Sump Pumps



Kit Part Nos.					
Series	Inlet	Exhaust	Discharge		
P35	251-K1	251-K2	251-K3		
P237	226-K1	251-K2	251-K3		

1 Air Inlet Kits

Part No.	Description	Quantity
251-K1		
XM-26	Male Coupling 1"	3
X-25	Hose Coupling 25mm	2
G	Safety Collar 25mm	2
8LUB16CA3	Lubricator	1
XM-26	Male Coupling 1"	2
6126	Valve 1"	1
25-39	Hose 25mm	1
226-K1		
XM-20	Male Coupling ¾"	3
X-19	Hose Coupling 19mm	2
E	Safety Collar 19mm	2
8LUB16CA3	Lubricator	1
XM-26	Male Coupling 1"	2
6120	Valve ¾"	1
19-31	Hose 19mm	1

2 Exhaust Kits

Part No.	Description	Quantity
251-K2		
R-3326	Male Coupling for Hose	1
PDA125-SHC	Safety Collar	1
40-58-5M	Hose 40mm	1

3 Discharge Kits

Part No.	Description	Quantity
251-K3		
SF-CD	Fitting	1
251-KSBF	Female Hose Connector	1
251-SHC	Safety Collar	2
251-DH20	Discharge Hose 2"	1

For Sump Pump Repair Kits please refer to Operation and Maintenance Manuals

Diaphragm Pumps

ARO-STOP Valve



Air Line Connection Kit



High Flow Pump Air **Motor Mufflers**



Screened Inlet Adapter Kits



Description	USCU V	vitti ivioaci ivo.
Pump overrun contro off air to pump when material container is or line is broken. Qui and reset feature incl	Pump empty 3" Pum ck set	os
Kit includes Piggybac Filter/Regulator with g pipe nipple and 1.5m section of air hose.	gauge, (Non-Met	allic) Illic 66312
Muffler helps reduce sound levels and ass ice-free operation. Me 94810 is recommend continuous duty oper Model 94117 is used intermittent duty oper	ures Pump odel (All other p sizes, mu ed in include rations. standar in	os (Cont. Duty) coump uffler 94117 ed (Interm. Duty)
Carbon steel, E-Coat screen prevents unw solids from entering I Kit includes hardward easy, quick attachme	anted Aluminium oump. 2" Port e for Aluminium 3" Port	Pump ts 67174-20 Pump ts 67174-30

Air Section Repair Kits

1½" Pumps 637118-2 2" & 3" Pumps 637302 Fluid Section Repair Kits 1½" Pumps 637124-22 2" Pumps 637309-AA

pump

For complete Diaphragm Pump performance and dimensions, refer to catalogue no. 9333-P



3" Pumps

637303-AA

Accessories and Service Kits

For Lubrication and High Pressure Cleaning Equipment and Tyre-Fill Pump Packages

High Pressure Grease Control Handles for LP3001, LP3007, LP3003 and LP3005



Description	Maximum Working Pressure	Fluid Inlet	Fluid Outlet
	bar	NPT	
For use with direct piping of product to wall station. Includes: 636111 high-pressure control handle 636077 "Z" swivel 624201-15 hose (4.6m)	345	⅓ (M)	Hydraulic Coupler
Model No.			615154
Dispenses lubricant at line pressure for lubricating grease fittings. Includes: Inlet material filter Curved nozzle with hydraulic coupler	517	% (M) or % (F)	Hydraulic Coupler
Remove the ¼ (M) x ¾ (M) adapter for ¾ (F) porting			

For ARO-PAK 640110



High-pressure booster handle delivers line pressure for normal lubrication. Trigger booster feature delivers 689 bar to break loose tougher fittings. Includes:

includes:

Model No.

Curved nozzle with hydraulic coupler Inlet material filter Manual pressure vent for easy disconnection.

Warning: Do not use with whip hose!

Model No. 636103

Bung Adapter Seal Kit

Water tight seal kit makes Thunder usable in all working and weather conditions i.e. oil rigs. For oil package 67088-4

Model No. 67088

Tie-Down Bracket Kit

Kit fixes/holds down cover on 60 litre/50kg. containers. Kit includes brackets, drum & tie rods and mounting hardware.

Model No. 640164

Airline Connection Kit

Includes "mini" air filter/regulator assembly. Kit includes piggyback, filter/regulator with gauge. pipe nipple and 5ft section of hose

Model No. 66073-1

Low Level Cutoff

½ (M)

or % (F)

For 2" 3:1 oil pump.

Model No. 67086

636111

Hydraulic

Coupler

Part No.	Description	Inlet thread	Length	Maximum Working Pressure
			mm	bar
Hydrauli	c Adapters			
629713	Extra capacity hydraulic extension adapter has flexible rubber hose. Use with standard hydraulic coupler	% NPT (M)	304	345
636003	Hydraulic adapter has locking sleeve to fit standard diameter coupler	-	177	552
636039	Hydraulic adapter has locking sleeve for use on nozzle, hose or adapters wit % NPT (M). Push on, pull off connector fits standard diameter hydraulic fitting		-	552
636065	Needle point adapter has rubber tip	-		552
Standard	Hydraulic Couplers			
636027	Small diameter hydraulic coupler	1/8 NPT (F)	41	414
636028	Reversible jaw hydraulic coupler	1/8 NPT (F)	41	689
636030	Hydraulic coupler and tube	11/16 - 16 NPT (F)		
636037	Hydraulic coupler and tube	½ NPT (F)	159	
636046	Small diameter hydraulic coupler with ball check	% NPT (F)	37	414

Repair Kits

517

керап	KIIS
Part No.	
Gear Oil an	d Grease Pumps for complete pump
637226	For LP3100-2
637227-B	For LP3001-1, LP3003-1, LP3005-1, LP3007-1
Tyre-Fill Pu	mps
637118-C	Air Motor
637119-41-C	Fluid Section
Wash Pump	OS .
61268	For Air Motor - 613104
637001	For Fluid Section - 613104
66614	For Air Motor - 613117-B
637211-K33	For Fluid Section - 613117-B



High Pressure Cleaning



Air Operated Pumps for water removal

PAGE 5




PAGE 3

Submersible Pumps



PAGE 2



Greasing and Oiling



PAGE 4

Calcium Chloride Tyre-Fill



PAGE 5

Portable Self-Contained Lubricators



PAGE 4

Ingersoll-Rand European Sales Limited
5-7 Avenue Albert Einstein, Zone Industrielle, 78192 Trappes, France
Tel: +33 (0)1 34 82 29 00 Fax: +33 (0)1 34 82 29 01

The Ingersoll-Rand distributor network gives you not only a superior product, but also a Total Quality service, to ensure your complete satisfaction.

For additional information about the products shown in this brochure, and assistance with selection, please contact your nearest Ingersoll-Rand distributor.

Nothing contained within this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other items or conditions of sale of products shall be in accordance with Ingersoli-Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoli-Rand. Designs and specifications are subject to change without notice or obligation.

Form No. E71002 CPN 00850008 Printed in England ©1999 by Ingersoll-Rand Company DISTRIBUTOR