

Vertical Turret Milling Machines



Brand Available: • Hercules • Armstrong • Precicut • 1K Taiwan
• Argo

Features :

- ▶ Table Guideways with High Stability
- ▶ Induction Hardened and Ground Table Surface
- ▶ Automatic Feeds on X and Y axis (Optional)

SPECIFICATION	10x50(3S)	10x54(4S)
Working surface	1270x254	1370x254
Longitudinal travel (Manual)	850	950
Longitudinal travel (Power feed)	850	950
Cross travel	400	400
Vertical travel	435/500	435/500
Overarm travel	600	600
T. Slots (width x number)	15.87x3	15.87x3
Spindle Speed 16	60-4500pm	
Quill travel	127	127
Quill feed (per revolution of spindle)	0.04/0.08/0.15mm/REV	
Spindle taper	R-8/ISO30/ISO40	R-8/ISO30/ISO40
Table to spindle nose	42-405	42-405
Head 45° - Forward & Reverse	--	--
Overarm swivel	360°	360°
Swivel angle of spindle head R/L	90°	90°
Spindle Motor	3 HP	3 HP
Rapid traverse motor (Optional)	0.5 HP	0.5 HP
Coolant pump	0.11 Kw	0.11 Kw
Net weight (Kg)	1000	1200