# **SERVO**<sup>®</sup> product data sheet SERVOFRIZ

## IndianOil

#### **GRADES AVAILABLE - SERVO FRIZ 12, 22, 32, 46, 68, 100**

<b>DESCRIPTION</b> Servofriz oils are high quality mineral lubricants formulated for the lubrication of reciprocating and rotary refrigeration compressors. These oils possess inherent resistance to oxidation and deposit formation.	APPLICATION Servofriz oils are recommended for the lubrication of a wide range of refrigeration compressors. These oils can be used with conventional refrigerants, except sulphur di-oxide, in both reciprocating and rotary compressors.
PERFORMANCE BENEFITS	and well maintained refrigeration systems, where evaporator temperatures are lower than the pour
• Possess high fluidity at very low	point of the oil.
<ul> <li>temperatures</li> <li>Resist deposit formation thereby keeping compressor parts clean</li> <li>Reduce compressor valve maintenance due to less deposits</li> <li>Ensure high condenser efficiency</li> <li>Have long service life due to high oxidation and thermal stability</li> <li>Have reduced tendency to foam</li> <li>Minimise copper plating due to their resistance to interact with metals in the system</li> </ul>	<ul> <li>PERFORMANCE STANDARDS         <ul> <li>Servofriz oils meet the following specification:                 <ul></ul></li></ul></li></ul>

#### CHARACTERISTICS

ISO VG	12*	22	32	46	68	100
Kinematic Viscosity, cSt @ 40 °C	12-14	20-24	33-35	43-46	63-65	90 - 100
Flash Point (COC), °C Min.	140	150	154	160	170	200
Pour Point, °C Max.	(-) 39	(-) 45	(-) 30	(-) 27	(-) 24	(-) 24

### \* Non ISO VG

#### **HEALTH & SAFETY**

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051 E-Mail: tservices@indianoil.co.in OR tech\_services@indianoil.co.in