

IndianOil

GRADES AVAILABLE – SERVO QUENCH 11 & C11

DESCRIPTION

Servoquench 11 and Servoquench C11 oils are high quality oils developed for general purpose metal quenching operations.

Theses oils are formulated from specially selected high viscosity index base stocks having good oxidation stability, good fluidity and low volatility. Servoquench 11 is a straight mineral oil having normal quenching characteristics. Servoquench C11 is incorporated with a polar additive, which imparts accelerated quenching property to the oil so as to meet certain specific end use requirements.

PERFORMANCE BENEFITS

Servoquench C and C 11

- Have good quenching characteristics
- Have long service life due to excellent oxidation stability
- Impart uniform hardness without distortion
- Have a wide application range

APPLICATION

Servoquench oils are used for all normal quenching operations on a wide variety of steel to impart the desired hardness to components without distortion. The special compounding agent incorporated in Servoquench C11 improves the wetting ability of the oil, so that it provides faster initial cooling for optimum hardness, where as the base oil ensures slow cooling in the final stage for stress relief and distortion free results.

Servoquench 11 is normally used for hardening nuts, bolts, ball bearings and certain types of brake drums as well as many other components manufactured by automobile and light engineering industries. Servoquench C11 is suitable for hardening of a variety of ball bearings, high speed steel tools, and other components in major industries

PERFORMANCE STANDARDS

Servoquench 11 meets IS: 2664-1980 (Reaffirmed 1993) for straight mineral type

medium grade quenching oil

Servoquench C11 meets IS: 2664-1980

(Reaffirmed 1993) for additive type quenching oil

CHARACTERISTICS

GRADE	11	C11
Kinematic Viscosity, cSt @ 40°C	27-33	27-33
Viscosity Index, Min	95	95
Flash Point (C)OC), °C Min.	200	200
Pour Point, °C Max.	0	0
Compounding		Yes

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR: