



Available on
GeM
Government
e Marketplace



Digital Podium

Equip yourself for an absolute presentation Control



DP 200L



★ ★ ★ Advanced Feature



Interactive Panel (21.5 inch) with motorized tilt control



Central Controller



RFID Authentication



Inbuilt PC



Keyboard Rack



Customized Branding on Acrylic Sheet



Movable Locking Board



Wireless Microphone Receiver



Gooseneck Microphone



Central Control Panel



Cabinet space for visualiser



Caster wheels

Ideal for Classrooms, Auditoriums, Universities, Polytechnics, Board Rooms, ITIs, Offices, Engineering/Medical Colleges, Ops Room, Training Rooms, Conference Rooms etc.

Specifications - Electronic Lectern

DP 200L

Type/Mounting	Free standing, wheel mounted
Construction	Polymer powder coated steel body, wooden top panels (with lock and key), sliding cover, all directional wheel with lock, cooling fans, tropicalised for Indian environmental conditions.
Display	
Monitor	Built-in highly sensitive Interactive Touch Panel with power driven motorized system to tilt adjust
Screen Type	LED
Size	21.5" (54.61 cm)
Resolution	1920 x 1080
Aspect Ratio	16:9/ 16:10
Interactive Resolution	4000 LPI
Computer Interface	USB x 1, VGA/ DVI/ HDMI x 1
Response Time	5 ms
Viewing Angles	170(H); 160(V)
Reading Accuracy	±0.5 mm (center)
Tracking Speed	200 points/sec. (Approx.)
Pen Pressure Sensitivity	2048 Levels
Touch Input	Finger / Stylus
Speakers	Inbuilt Speakers
Console Panel Ports	RGB x 1, HDMI x 1, USB, RJ45 LAN PORT, Display Switcher, Video Input
Annotation Software	Features like draw, choose, pens, annotate, erase, color, shapes, sizes, text, edit, fonts, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard, background etc.
Built-In	
Devices	Permanently polarized phantom powered Gooseneck Mic (21.5cm) with XLR output and ON/OFF switch (with LED indication) x 1, Cordless Collar Mic x 1, Wireless Receiver x 1 (15 mtr range), Handheld Mic x 1
Central Controller with Panel	VGA x 2, Audio x 2, Video x 2
Amplifier	Power: 100 Watts
Speakers (External)	Speakers x 2, RMS: 50 watt, Frequency Response: 100Hz to 15KHz, Sensitivity: +30dB
AV Switcher	Input: RGB x 2, RCA x 2; Output: RGB x 2
Security	Single physical key for all locks, RFID authentication System for secure access to system (Central Locking), Password Protection
System Details	
Processor	3.2 GHZ, 3 MB Cache with compatible chipset on Industrial grade chasis (small form factor)
Memory	4 GB
HDD/Storage	1 TB
Expansion I/O	4 USB, 1 Serial, LAN 10/100/VGA
Audio	Line-in x 1/ Line-out x 1
Keyboard and Mouse	Wireless Keyboard and Mouse provided
O/S	Windows 10 SL
Environment	
Operating Temperature	5°C ~ 40°C, 90% RH at 40°C
Storage Temperature	-10°C ~ 55°C, 90% RH at 40°C
Power	
Power Supply	180 - 240V, 50Hz, AC
Power Consumption	120 Watt (Max)
Provision for Additional Devices	A dedicated space to house CPU/Laptop with Security Lock, Sliding Tray, Sliding Shelf for visualizer, Space for Keyboard and mouse, Logo on Acrylic Sheet

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

C -1/2, Safdarjung Development Area, New Delhi - 110016

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

Toll Free: 1800-200-4398



Available on
GeM
Government
e Marketplace

