



Digital Insulation Tester **D20K**

FEATURES

- Display- 3½ Digit LCD with max. reading of 1999 counts.
- Automatic zero adjustment.
- Selectable test voltage of 500V/ 1000V/ 2000V/ 2500V DC.
- Resistance measurement upto 20000MΩ across all the four test voltages.
- Fast and accurate readings.
- Short circuit current $\leq 1.5\text{mA}$.
- Low Batt Indication : LOBAT is displayed.
- Power : 1.5V x 6 Nos. Battery Type AA or equivalent.
- Dimensions : Approx 175 (L) x 115(W) x 55 (H) mm.
- Weight : 500 gm.(approx.).
- Over range indication : Most significant digit "1" is displayed.

SPECIFICATIONS:

Test Voltage (DC)	500V	1000V	2000V	2500V
Accuracy (measured using High Voltage Probe/Meter having input Impedance of $\geq 1000M \Omega$)	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$
Output voltage variation w.r.t. load variation	90% to 110% of selected test voltage.			
Resistance range	10-20000M Ω	10-20000M Ω	10-20000M Ω	10-20000M Ω

- Accuracy : 10~10000M Ω ($\pm 5\%$ + 5 digits.)
10001~ 20000M Ω ($\pm 10\%$ + 5 digits.)
- Short circuit current : $\leq 1.5mA$.
- Withstand voltage : AC 2KV 50 Hz for 1minute, applied between all terminal shorted and case.

STANDARD ACCESSORIES

- One Set of Earth Lead of 1 mtr.
- Line and Guard Leads of 1 mtr.
- Instruction Manual.
- Carrying Case.

APPLICATIONS

Testing of low and medium rating transformers, motors, cables, switches, wiring, etc.
Measuring insulation resistance of dielectric materials.
Maintenance and periodic check of electrical equipments.



we have a solution....

DBS/PC/IR-02/Rev-02

NOTES 1.The Instrument is accompanied with Test & calibration sheet. 2.Test Facilities can be provided at the factory with the available test set-ups only. 3.The Company's policy is continuous improvement of its products. we therefore reserve the Right of any deviation from illustration or specifications without notice. 4.Stated accuracies are valid from 1/10th of range to FS. 5.Accuracy Specified for temperature range of $25^{\circ}C \pm 5^{\circ}C$ & 55%RH $\pm 10\%$.



The Motwane Manufacturing Company Pvt. Ltd.

REGD. OFF. & FACTORY : Gyan Baug, Motwane Road, Nashik Road-422101
Tel.: +91 - 253 - 2463752 / 53 Fax.:+91 - 253 - 2463197 e-mail: sales@motwane.com Toll Free No.:18002332222

MUMBAI : 223-224, MIDAS, Sahar Plaza, Andheri - Kurla road, J. B. Nagar, Andheri (E), Mumbai – 400059
TEL: +91-22-40155585 / 6 / 7 FAX: +91-22-40155588 e-mail: mumbai@motwane.com

DELHI : 2 D, 2nd Floor, Vandana Building, 11, Tolstoy Marg, Cannaught Place, New Delhi - 110 001
Tel.: +91 - 11 - 41522 105 Fax.: +91 - 11 - 41522 106 e-mail: delhi@motwane.com

BANGALORE : #8 / 12, 3rd Floor, Honnam Complex, South Cross Road, Basavanagudi, Bangalore - 560 004.
Tel.: +91 - 80 - 26611323 Fax.:+91 - 80 - 26621186. e-mail: bangalore@motwane.com

KOLKATA OFFICE : Eden Terrace , 10 , Tarak Datta Road, Near Beck Bagan Methai, Kolkata – 700019.
Tele Fax : +91-33-22832436. FCT Land Line : +91-9007791374. E-mail:Kolkata@motwane.com



To make enquiry please visit www.motwane.com and click 'Make an enquiry'.

Represented by

