

Conventional Manual Call Point

MODEL: **BG-ABS-2**

BG-ABS-2 is a call point designed to provide a manual alarm interface to any conventional fire alarm control panel. ASES call point is having two different switches - one for alarm activation and another for alarm Reset. Bicolour LED indication shows the stats of the call point - GREEN for healthy condition and RED for fire condition. All indoor call point products also help preserve the integrity of the overall system as illegal removal of the product will result in the call operating and the system going into fault condition. All the MCP comes with a factory fitted back box for surface or semi-finish mounting on the wall.



Features:

- **Re-settable operation**
- **Compatibility with any make conventional fire alarm system**
- **Wall mount facility**
- **At normal Green-LED blinking duration of 14 sec**
- **Steady glow of Red LED indicates the alarm condition**
- **Suitable for malls, restaurant, residential etc.**

Specification:

Operating voltage	24V DC
Current Consumption (Normal/fire)	150µA/ 60mA@ 24 VDC
Application Temp range	0° C to + 60° C
Humidity	5 to 95% Relative Humidity (non condensing)
Housing	ABS
Weight	80gm
Dimensions (mm)	100 x 93 x 33 (W x H x D)
Colour	Red

Operation:

Blinking of green LED indicates the healthy condition of MCP. To operate the MCP flip the plastic cover, press the alarm switch. Steady glow of Red LED confirms the activation of alarm. To reset the MCP, press the reset switch, Red LED will stop glowing & green LED will start blinking

Ordering Information

Part Number	Pack Quantity	Dimensions (WxHxD millimetres)	Weight
BG-ABS-2	Individual(1 units)	100 x 95 x 52	100g