



## Interior Emulsion

### PRODUCT DESCRIPTION

Indigo Interior Emulsion is a specially developed economical product with a smooth finish and better whiteness, opacity and coverage as compared to normal distemper. It is formulated by using ideal combination of pigments and extenders, dispersed in a copolymer emulsion for smooth and pleasant matt finish.



### PERFORMANCE FEATURES & BENEFITS

Economical Emulsion

#### FINISH

**MATT**

GLOSS

#### WASHABILITY

**NO**

LOW

MEDIUM

HIGH

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

Concrete & Walls

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Shake well before use

#### TOOLS



Brush & Roller

#### THINNING



Water

#### THINNING RATIO



50-55% by Volume

#### SURFACE DRYING TIME



Surface Dry in 30 Min.

#### FILLING



Indigo Polymer Putty or Acrylic Wall Putty

#### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 70%

#### CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper.  
Wipe clean with a soft cloth.

#### SURFACE PREPARATION



Apply Indigo Cement Primer. After drying for 8 hours, fill the dents in the surface with Polymer Putty. Repeat sanding with emery paper, wipe clean, and apply another coat of Indigo Cement Primer. After drying for 8 hours, sand with fine emery paper & wipe clean.

#### APPLICATION



Apply 2-3 coats of Indigo Interior Emulsion, obtained by thinning 1 litre of emulsion with 500-550 ml of water.

#### SAFETY FEATURES



Non- flammable  
No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

<b>Coverage</b>	1 Coat: 150 - 160 sqft/ltr* 2 Coat: 90 - 100 sqft/ltr*
<b>Drying Time</b>	4-5 Hrs
<b>Sheen level</b>	2.4 at 60 degree
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24 Hrs
<b>Appearance</b>	Smooth, Liquid, White
<b>Solids</b>	50 %
<b>Specific gravity</b>	1.38
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by Stormer Viscometer</b>	1900 CP
<b>Pot life</b>	24 hrs
<b>Shelf life</b>	24 months
<b>Contrast ratio</b>	93.55

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

## PRECAUTIONS

1. Wall should be free from moisture
2. If any wall is under seepage, treat it with proper waterproofing
3. Do not apply on any lime washed surfaces
4. In case of fungi or algae use Indigo Bio Clean to clean the surface

## POST APPLICATION INSTRUCTIONS

NA

## AVAILABLE PACK SIZE

Available in:



## SHADE RANGE

As per Indigo Colour Fandek



**INDIGO**  
Be surprised!