

Bright Ceiling Coat

PRODUCT DESCRIPTION

Indigo Bright Ceiling Paint is specially formulated to provide minimal spatter and excellent coverage with High Brightness. It hides minor surface imperfection and dries quickly to give a smooth even finish.



PERFORMANCE FEATURES & BENEFITS

1. Uniform finish
2. High Brightness
3. Easy to apply
4. No Odour

FINISH

MATT

SEMI GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA

Interior Ceiling

SURFACES

Concrete, Plastered walls and Interior Ceilings

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush, Roller & Spray

THINNING



Water

THINNING RATIO



50-60% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



Sand the surface with Emery paper 180 and wipe clean.

SURFACE PREPARATION



Apply a coat of Indigo Primer, allow drying for 6-8 hours. Smoothen the surface by filling dents with thin coats of Indigo Acrylic Wall Putty. After drying for 6-8 hours, sand the surface with Emery paper 180. Wipe off loose particles. Apply another coat of primer. Allow drying for 4-6 hrs. Sand the surface with Emery paper 380 and wipe clean.

APPLICATION



Apply 2-3 coats of Indigo Bright Ceiling Coat, obtained by thinning 1 litre of emulsion with 500-600 ml of water.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

| | |
|--|--|
| Coverage | 1 Coat: 100 - 120 sqft/ltr* 2 Coat: 65 - 75 sqft/ltr* |
| Drying Time | 4-5Hrs |
| Sheen level | 2.4 at 60 deg |
| Flash point | NA |
| Stability of thinned paint | 24Hrs |
| Appearance | Smooth, Liquid, Milky White |
| Solids | 54 |
| Specific gravity | 1.39 |
| Recommended DFT | NA |
| Viscosity @25°C by Stormer Viscometer | 2200 CP |
| Pot life | 24 Hrs |
| Shelf life | 24 Months |
| Contrast ratio | 98.79 |

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Wall should be free from moisture
2. If any wall is under seepage, treat it with proper waterproofing
3. Do not apply on any lime washed surfaces
4. In case of fungi or algae use Indigo Bio Clean to clean the surface

POST APPLICATION INSTRUCTIONS

1. Painted surfaces can be washed after 30 days with mild detergent and cellulose sponge.
2. Do not use harsh, abrasive cleaners.


AVAILABLE PACK SIZE

Available in:



SHADE RANGE

White



INDIGO
Be surprised!