

Exterior Emulsion

PRODUCT DESCRIPTION

Indigo Exterior Emulsion brings you the latest technology in exterior coatings at an economical price. It is a water thinnable wall coating for exterior surfaces, which will not fade for years. It is Durable & Washable Paint which provides rich Smooth finish and will last longer.



PERFORMANCE FEATURES & BENEFITS



Anti-algal

- Excellent resistance to chalking, cracking and weathering in comparison to cement paint.
- It gives neat and clean shades

FINISH

MATT

GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Concrete, walls and Masonary Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush, Roller & Spray

THINNING



Water

THINNING RATIO



65-75% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING



Clean the surface of loose paint, dust and grease. Scrub vigorously with wire brush to remove algae, fungus and moss growth, especially on horizontal surfaces prone to water stagnation.

SURFACE PREPARATION



Seal cracks with a 1:3 mixture of cement and sand. Use of Indigo Polymer Putty is highly recommended. Allow 3 months curing prior to painting for newly plastered surfaces. Freshly plastered surfaces require a self-priming coat, obtained by thinning 1 litre of paint with 1 litre of water.

APPLICATION



Apply 2 coats of Indigo Exterior Emulsion, obtained by thinning 1 litre of emulsion with 650-700 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 110 - 125 sqft/ltr*
	2 Coat: 60 - 75 sqft/ltr*
Drying Time	4-5Hrs
Sheen level	2.2 at 60 deg
Flash point	NA
Stability of thinned paint	24Hrs
Appearance	Smooth,Liquid, White
Solids	61
Specific gravity	1.3 to 1.49
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2100 cp
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	98.5

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Do not apply in rainy season, apply only on properly dry surface
2. Tinted paint needs to be shaken immediately after tinting

POST APPLICATION INSTRUCTIONS

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

AVAILABLE PACK SIZE

Available in:



500 ml



1 Ltr



4 Ltr



10 Ltr



20 Ltr

SHADE RANGE

As per Shade Card & Indigo Colour Fandek



INDIGO

Be surprised!