

Exterior Wall Primer

PRODUCT DESCRIPTION

Indigo Exterior Wall Primer is a water-based under coating to an emulsion paint and is suitable for application on exterior walls.



PERFORMANCE FEATURES & BENEFITS

- 1. Execellent opacity 2. Excellent whiteness and adhesion to top coat emulsion
- 3. Does not chalk and does not require any water curing



RECOMMENDED USES

AREA





SURFACES

Cement plasters, Exterior ceilings, Asbestos sheets, Concrete, Brickwork, etc

APPLICATION DETAILS & SURFACE PREPARATION




















Remove all dust, dirt, chalking, oil, grease, loose particles and all other contamination. Any previous growth of fungus, algee should be removed by wire mesh and clean with water.

SURFACE PREPATION



NΔ

APPLICATION



Apply 1-2 coats depending on surface condition.

SAFETY FEATURES



Non- flammable No added Lead, Mercury or Chromium compounds

TECHNICAL DATA	
Coverage	1 coat-110-130 sq.ft/Lt.*
Drying Time	4-5 Hrs
Sheen level	2.0 at 60 degree
Flash point	NA
Stability of thinned paint	24 Hrs
Appearance	Smooth, Liquid, White
Solids	52 %
Specific gravity	1.4
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2300 CP
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	95.8

^{*}Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

In coastal areas, do not leave primer without application of top coat

Do not over thin

POST APPLICATION INSTRUCTIONS

Apply Indigo Exterior Emulsion on Primer

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

White



For more information on our products and services contact 02931 281 162 or visit us at www.indigopaints.com INDIGO Paints Pvt Ltd, 103 Montreal, Baner Road 411 045, India