



Acrylic Laminate

PRODUCT DESCRIPTION

Indigo Acrylic Laminate is an acrylic latex based paint which gives rich sheen finish. It is suitable for both Interior & Exterior surfaces.



PERFORMANCE FEATURES & BENEFITS



Rich Sheen Finish



High Stain Resistance



Anti-fungal & Anti-algal



Easy to clean
(For Interior surfaces)

FINISH

MATT

SEMI GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Concrete, Brick and other Masonary Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



35-40% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING



Clean the surface of loose paint, dust and grease. Scrub vigorously with wire brush to remove algae, fungus and moss growth, specially on horizontal surfaces prone to water stagnation.

SURFACE PREPARATION



Seal cracks with a 1:3 mixture of cement and sand. Use of Indigo Polymer Putty is highly recommended. Allow 3 months curing prior to painting for newly plastered surfaces. Apply one coat of Indigo Wall Primer on the plastered surface.

APPLICATION



Apply 2 coats of Indigo Acrylic Laminate, obtained by thinning 1 litre of laminate with 350-400 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 200 - 210 sqft/ltr* 2 Coat: 130 - 150 sqft/ltr*
Drying Time	4-5Hrs
Sheen level	21.4 at 60 deg
Flash point	NA
Stability of thinned paint	24Hrs
Appearance	Smooth, Liquid, Milky White
Solids	49
Specific gravity	1.24
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2200 CP
Pot life	24 Hrs
Shelf life	24 Months
Contrast ratio	98.17

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Do not over thin
2. Tinted paint needs to be shaken immediately after tinting

POST APPLICATION INSTRUCTIONS

1. Remove all dirt using a clean cloth / duster
2. Always remove dirt from top to bottom

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per shade card and Indigo Colour Fandek.



INDIGO
Be surprised!