



Metallic Emulsion

PRODUCT DESCRIPTION

Indigo Metallic Emulsion is a revolutionary Paint, suitable for exterior as well as Interior walls. It is based on a pure Acrylic formulation and it gives sparkling metallic texture to the walls.



PERFORMANCE FEATURES & BENEFITS



High Sheen

Excellent glitter

FINISH

MATT

SEMI GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Wood / Metallic / Concrete

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



25-35% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



For exterior surfaces, scrub with wire brush and clean the surface of loose paint, dust and grease. For interior surfaces, clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

SURFACE PREPARATION



NA

APPLICATION



Apply a priming coat of Indigo Water Thinnable Cement Primer. Follow with 2 coats of Metallic Emulsion, obtained by thinning 1 litre of paint with 250-300 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1st Coat-100-110 sq.ft/ltr* 2nd Coat- 60-70 sq.ft/ltr *
Drying Time	4 - 5 Hours
Sheen level	39.9 at 60 degree
Flash point	NA
Stability of thinned paint	24 Hrs
Appearance	Liquid
Solids	35
Specific gravity	1.1
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2279 cp
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	89.81

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

Do not dilute with thinner

POST APPLICATION INSTRUCTIONS

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Shade Card

