



## Premium XT Exterior Emulsion

### PRODUCT DESCRIPTION

Indigo Premium XT Exterior Emulsion is specially designed to withstand extreme weather conditions with superior anti-fungal and anti-algae properties.



### PERFORMANCE FEATURES & BENEFITS



Weather Guard



Dirt Pickup Resistance



Anti-fungal & Anti-algal

### FINISH

**MATT**

GLOSSY

### WASHABILITY

NO

LOW

MEDIUM

**HIGH**

### RECOMMENDED USES

#### AREA



INTERIOR



EXTERIOR

#### SURFACES

Concrete, Walls and Masonary Surface

### APPLICATION DETAILS & SURFACE PREPARATION

#### MIXING



Shake well before use

#### TOOLS



Brush, Roller & Spray

#### THINNING



Water

#### THINNING RATIO



40-50% by Volume

#### SURFACE DRYING TIME



Surface Dry in 30 Min.

#### FILLING



Indigo Polymer Putty or Acrylic Wall Putty

#### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 80%

#### CLEANING



Clean the surface of loose paint, dust and grease. Scrub vigorously with wire brush to remove algae, fungus and moss growth, especially on horizontal surfaces prone to water stagnation.

#### SURFACE PREPARATION



Seal cracks with a 1:3 mixture of cement and sand. Use of Polymer Putty is highly recommended. Allow 3 months curing prior to painting for newly plastered surfaces. Apply 1 coat of Indigo Exterior Wall Primer, obtained by thinning 1 litre of primer with 1 litre of water.

#### APPLICATION



Apply 2 coats of Indigo Premium XT Exterior Emulsion, obtained by thinning 1 litre of laminate with 400-500 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

#### SAFETY FEATURES



Non- flammable  
No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

<b>Coverage</b>	1 Coat: 110 - 130 sqft/ltr* 2 Coat: 70 - 80 sqft/ltr*
<b>Drying Time</b>	4-5Hrs
<b>Sheen level</b>	2.2 at 60 deg
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24Hrs
<b>Appearance</b>	Smooth, Liquid, White
<b>Solids</b>	61
<b>Specific gravity</b>	1.3 to 1.49
<b>Recommended DFT</b>	NA
<b>Viscosity @25°C by Stormer Viscometer</b>	1900 CP
<b>Pot life</b>	24 hrs
<b>Shelf life</b>	24 months
<b>Contrast ratio</b>	98.5

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

## PRECAUTIONS

1. Do not apply in rainy season, apply only on properly dry surface
2. Tinted paint needs to be shaken immediately after tinting

## POST APPLICATION INSTRUCTIONS

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

## AVAILABLE PACK SIZE

Available in:



## SHADE RANGE

As per Shade Card & Indigo Colour Fandek

