



Sealer Primer

PRODUCT DESCRIPTION

Indigo Sealer Primer is a water-based under coating to an emulsion paint and is suitable for application on both interior & exterior walls. It has excellent sealing properties and good resistance to dampness, efflorescence and alkali. Provides excellent bonding with surface and with topcoat emulsion.



PERFORMANCE FEATURES & BENEFITS

- Superior Hiding
- Excellent Whiteness

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Concrete, Brick & other Mansory Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush

THINNING



Water

THINNING RATIO



75-85% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft cloth.

SURFACE PREPARATION



NA

APPLICATION



Apply 1-2 coats depending on surface condition.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1 coat-110-140 sq.ft/Lt.*
Drying Time	4-5 Hrs
Sheen level	2.2 at 60 degree
Flash point	NA
Stability of thinned paint	24 Hrs
Appearance	Smooth, Liquid, White
Solids	52.6 %
Specific gravity	1.4
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2300 CP
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	98.7

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

Do not leave primer without application of top coat

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

White



INDIGO
Be surprised!