

Acrylic Distemper (Pouch)

PRODUCT DESCRIPTION

Indigo Acrylic (Pouch) Distemper is an economical paint with very bright colors.



PERFORMANCE FEATURES & BENEFITS

- Economical
- Bright Shades

FINISH

MATT

GLOSSY

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Plastered Walls

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



70% by Volume

SURFACE DRYING TIME



Surface Dry in 20 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



Clean and remove loose plaster or dust using sand paper.

SURFACE PREPARATION



NA

APPLICATION



Apply two coats of Indigo Acrylic (Pouch) Distemper on walls.

SAFETY FEATURES



Non-flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1st Coat-110-120 sq.ft/Kg* 2nd Coat- 60-70 sq.ft/Kg *
Drying Time	3-4 Hrs
Sheen level	2.0 at 60 deg
Flash point	NA
Stability of thinned paint	NA
Appearance	Semi Solid
Solids	70
Specific gravity	1.73
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	400 by psi Penetrometer
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	97.5

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

Do not apply when the ambient temperature below 10°C. Do not apply directly on Lime wash or White cement painted wall

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



1 Kg

SHADE RANGE

As per Shade Card

