



Sleek XT Exterior Single Pack PU

PRODUCT DESCRIPTION

Sleek XT single pack PU Topcoat is a top quality product for the protection of all types of exterior wood work. Based on a modified PU binder and fortified with UV absorbers, it offers medium term protection for all types of exterior joinery under normal exposure conditions.



PERFORMANCE FEATURES & BENEFITS

- Fortified with UV Filters
- Repels Water
- Easy to use

FINISH

MATT **GLOSS** **SILK MATT**

MIXING RATIO

NA

RECOMMENDED USES

AREA

INTERIOR

EXTERIOR

SURFACES

It can be used on all types of exterior joinery (like doors, windows) furniture etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well before use

TOOLS



Brush, Spray

THINNING



Turpentine

THINNING RATIO

10-20% by volume

SURFACE DRYING TIME



30 minutes

FILLING



NA

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING



Ensure that the wood is seasoned and the surface is well-dried.

- To remove the oiliness inherent to tannin rich wood such as teak and rose wood, wipe clean with NC thinner.

SURFACE PREPARATION



- Sand the wooden substrate along the grains, sequentially, with abrasive paper from grit numbers 80 to 180.
- The dust, dirt that comes out during the sanding process should be totally removed.

APPLICATION



Apply 2 coats of Sleek XT single pack PU topcoat by brush / spray with 6-8 hours drying time between coats. Inter-coat sanding using abrasive paper grit no. 320.

SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	60-70 Sq.feet/Liter/Coat
Drying Time	6-8 hours
Sheen level	90-95° - Glossy 25-30° - SilkMatt 10-15° - Matt
Flash point	Above 34°C.
Stability of thinned paint	NA
Appearance	Clear
Solids	46+/-1%
Specific gravity	0.92
Recommended DFT	25 to 30 microns per coat
Viscosity @25°C by Stormer Viscometer	-
Pot life	NA
Shelf life	12 months
Contrast ratio	NA

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as type of substrate.*

PRECAUTIONS

- Flammable
- Keep away from heat, sparks etc.
- Use appropriate protection during application.
- Ensure adequate ventilation during application.

POST APPLICATION INSTRUCTIONS

-

AVAILABLE PACK SIZE

Available in:



500 ml



1 Ltr



4 Ltr



20 Ltr

SHADE RANGE

NA



INDIGO

Be surprised!