



Sleek Interior Single Pack PU

PRODUCT DESCRIPTION

Sleek single pack PU Topcoat is polyurethane based clear topcoat designed to be used for all types of interior wood work. It provides a durable film that protects furniture from water, alcohol and other household chemicals. It is available in glossy & matt finish and is resistant to wear.



PERFORMANCE FEATURES & BENEFITS

- Rich Finish
- Smooth feel

FINISH

MATT

GLOSS

SILK MATT

MIXING RATIO

NA

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

It can be used on all types of interior wood like doors, windows, furniture, kitchen cabinets etc.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Stir well before use

TOOLS



Brush, Spray

THINNING



Turpentine

THINNING RATIO

10-15% by volume

SURFACE DRYING TIME



30 minutes

FILLING



Sleek NC Sanding Sealer

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING



Ensure that the wood is seasoned and the surface is well-dried.

- To remove the oiliness inherent to tannin rich wood such as teak and rose wood, wipe clean with NC thinner.

SURFACE PREPARATION



- Sand the wooden substrate along the grains, sequentially, with abrasive paper from grit numbers 80 to 180.
- The dust, dirt that comes out during the sanding process should be totally removed.
- Apply 2-3 coats of Sleek NC Sanding Sealer

APPLICATION



Apply 2 coats of Sleek Single Pack PU Topcoat by brush or spray. Allow 6-8 hours drying time between coats.

SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	60-70 Sq.feet/Liter/Coat
Drying Time	6-8 hours
Sheen level	90-95° - Glossy 10-15° - Matt
Flash point	Above 34°C.
Stability of thinned paint	NA
Appearance	Clear
Solids	50+/-1%
Specific gravity	0.9
Recommended DFT	25 to 30 microns per coat
Viscosity @25°C by Stormer Viscometer	-
Pot life	NA
Shelf life	12 months
Contrast ratio	NA

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

- Flammable
- Keep away from heat, sparks etc.
- Use appropriate protection during application.
- Ensure adequate ventilation during application.

POST APPLICATION INSTRUCTIONS

-

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

Clear, Teak, Walnut, Oak Yellow



INDIGO
Be surprised!