



## **Technical Data Sheet**

1	Package Compressor Model	<b>TLT200C-30-50E</b>
2	Bare Compressor model	HLT200
3	Type of Compressor	Tank Mounted, lubricated, reciprocating compressor
4	Type of Motor	<b>20 HP, 3-phase</b> , T.E.F.C, foot mounted
5	Motor Speed	1440 rpm
6	Compressor Speed	1100 rpm
7	Piston Displacement	1618 lpm (57 cfm)
8	FAD	<b>1174 lpm (41.5 cfm)</b>
9	Working Pressure	<b>30 kg/cm<sup>2</sup></b>
10	Pressure Switch Cut-in pr.	25 kg/cm <sup>2</sup>
11	Pressure Switch Cut-off pr.	30 kg/cm <sup>2</sup>
12	Type of Starter	Star Delta starter
13	Tank Capacity	500 Lt
14	Overall Size (L x W x H) in mm	2020 x 810 x 1310
15	Type of Suction Filter	Dry type filter (Polyester)
16	Recommended Lube Oil	<b>aimair lube oil</b>

Date: 08.11.2011

Checked by:	Prepared by:  <b>ANIL KUMAR</b>
-------------	---------------------------------------

**Anest Iwata Motherson Ltd.**