

All Xenetech Graphic Workstation™ (XGW) software performs automatic Grade II Braille transcription with ADA compliant typefaces and logos.



A HIGHER STANDARD

Here are just a few of the standard features you can expect with every Xenetech rotary engraving system:

- High performance Viper electronics with touch screen key pad
- 10 ips and faster engraving
- Forward/backward by character, line and plate from Pendant
- DC motor speed control (AC motor speed control optional.)
- Longplate/fallplate engraving capable of engraving 13-5" (342.90mm) x 189" (4800 mm) in Longplate/fallplate
- State-of-the-art motion control system
- Two-year limited warranty, *extended warranty available.*
- Multi-plate and batch processing
- Automatic surface sensing on all machines (*standard*)
- Graphic job printouts
- Ability to engrave a wide variety of materials
- Routing capabilities
- Networkable
- Cylindrical attachment available
- 11/64", 1/4", 4 mm and 6 mm top-load and collet spindles available (*Collets available: 1/4" split or solid, 11/64" split or solid, 4mm split or solid, 6mm split or solid, 1/8" split, or 3/16" split*)
- X, Y and Z-axis resolution/repeatability standard: .000313", user selectable: .000625" and .000156"
- Spindle downfeed: mode 1) fully programmable via software, mode 2) downfeed manually set via control pendant, and mode 3) automatic surface sensing for downfeed
- Spindle motor: 1/4 hp spindle motor; 20,000 rpm at spindle
- Viper electronics connect to free ethernet connection


[†] Computer not included.

ROTARY


The XOT 1313 is capable of engraving into aluminum, brass and stainless steel.



Reverse engraved plastic and paint filled, this precise line detail is perfect for blueprint or industrial applications.



XOT 1313



XOT 1313 Big-time features in a smaller-format machine. Pound for pound, it's the strongest engraver in our line, a winning combination of power, performance and cost-effectiveness. It's our "leading seller" in the industrial markets, where engraving, routing and milling stainless steel and other difficult materials are often required.

Standard 2-year warranty.

Table surface area: 13-5" x 13-5" (342.9 x 342.9 mm) • Footprint: 22-5" x 27-5" (571.5 x 698.5 mm) • Engraving area: 182 sq. in. (4,622.8 sq. mm) • Shipping weight: 340 lbs. (154.36 kg) • Maximum spindle travel: 2" (50.8 mm); Maximum material clearance: 7.188" (182.5 mm) • Includes accessory pack with 5 plastic cutters (see page 22) • Call for further options and specs.

FOR PRICING, TECHNICAL SPECS OR ORDERING: 1-225-752-0225



Touch screen keypad: On-board control panel gives total control of the job and view of job statistics such as, scroll-through job queue, recall job, end-of-job signal, job time statistics, positioning and more.

FOR MORE INFORMATION AND XENETECH NEWS: www.xenetech.com



The Viper electronics work with our 912, 1313, 1625, 2525 and 2550 engraving tables, Viper® JE Jewelry Engraving System and Viper® GE Gift Engraving System. It's a cost-effective investment in productivity that simply can't be beat.

Xenetech's Viper® Electronics

A PARADIGM SHIFT IN ROTARY ENGRAVING

XENETECH HAS DEVELOPED AN EASY AND COST EFFECTIVE WAY FOR YOU TO SIGNIFICANTLY INCREASE YOUR EXISTING SYSTEM'S ENGRAVING SPEED (UP TO 3 TIMES) AND PUT THE TOTAL CONTROL OF EVERY JOB AT YOUR FINGERTIPS.

You can power your existing Xenetech engraving table at three times the current engraving speed (10 ips for 1313 and 1625, and 8 ips for 912, 2525, 2550, Viper® JE and GE).

The Xenetech Viper electronics plug in multiple engravers and utilize Ethernet communications which increases download speed and have a virtually unlimited job queue.

It's completely compatible with Xenetech's Engravelab™ print driver and shipped with XGW-32 professional engraving software.

The Viper's controller provides interpolation of all 4 axes simultaneously with on-board temperature, motor, and voltage diagnostics.

With the Viper Pendant, you have complete, touch-screen access to your engraving system. The hand-held key pad gives you the ultimate control to select jobs from the hard drive, engrave jobs forward/reverse by character, line, plate, and job), check XYZ positioning and digital readouts, override engraving speeds, program the z axis, record job timing, and more.

Just unplug your existing electronics, plug in the Viper and install the Viper driver on your laptop or desktop computer. You'll be engraving with record productivity within the hour.

COMPATIBLE SYSTEMS

912, 1313, 1625, 2525, 2550, Viper® JE and Viper® GE systems

Any system currently running on Xenetech electronics is compatible. This includes retrofits and Xenetech systems manufactured prior to 1995. The speed and letter quality will increase and improve on these systems, but they will not necessarily be able to reach the speeds attained by newer Xenetech tables.

Note: Any mechanical problems experienced must be resolved before upgrading to Viper electronics.

COMPUTER REQUIREMENTS

- Windows 98 or higher
- 10/100 network card or free network hub connection
- 100 MB free hard drive space
- 256 MB Ram
- Compatible with laptop and desktop computers



*Patent Pending

ELECTRONICS