



FIX FOAM CONCRETE ROAD/ CANAL PAVER FINISHER

Optional Accessories

- Longitudinal & transverse groove cutter
- Longitudinal & transverse pvc water stop inserter attachment
- Transport assembly
- Slope wedges
- Fabricated rail





Technical Specification

Model	
Prime Mover	
Driver End Panel	5 HP Geared Motor
Vibratory Cylinder	5 HP Geared Motor
Bogie RH & LH	1 HP + 1 HP Geared Motor
Vibratory motor	1 HP Electric Motor
Traction System	
Traction Drive	Two Electrically driven double flanged bogie wheels
Traction Speed	0-22 rpm
Vibratory Cylinder Under Carriage	
Finished Cylinder 270 mm dia., 1.2 Mtr. long precisely balanced	
Extra Long Screw Augur (RH & LH) with hardened flights	
Finishing Tolerance: + -3 mm in 12 ft.	
Machine Controls	
Adjustable Carriage Movement with Variable Speed Drive	
Shock Protection	
Overload Protection	
Construction	
Frame: All welded, pin connected main frame. Available in length of 2.40 mtr., 1.2 mtr., 0.6 mtr., which are infinitely adjustable up to 62 ft. (CE 200) and 110 ft. (CE 400)	
Finishing Width: Finishing width normally 3ft. (0.9 mtr.) less than frame width and adjustable from 1mtr. to 32 mtr.	